

MOE

Manhole Odor Eliminator

Patented

www.ManholeOdorEliminator.com

Installation Instructions For Adjustable Stainless Steel Funnels

Always follow appropriate safety precautions when servicing sewer manholes. This includes personnel protection, traffic, and ventilation precautions. Sewer gases are dangerous and contain hazardous, poisonous, flammable and explosive gases. Only experienced trained workers following OSHA's safety requirements should work around sewer manholes.

Place barrier cones at service area. Never leave a manhole uncovered and unsupervised.

Remove manhole cover. Clean frame under cover. Measure and double check frame size and type before insert is installed.

Test stainless steel adjustable funnel fit by placing lightly on frame. If not sitting flat inspect for any obstructions or irregularities. A sponge gasket or silicone may be used to help create a tight seal. Expand funnel to fit manhole and tighten locking bolts.

Drop housing into funnel and check to insure a tight fit and then install drop in carbon cartridge.

The life of the odor absorbing cartridge at each manhole varies depending on the sewer system activity, sewer gas concentration and ambient conditions.

When multiple MOE units are used at one site it is recommended that spare cartridges be available for problem areas.

Contact Inventive Resources, Inc. at 209-545-1663 to order replacement cartridges. Cartridges are recommended to be replaced every 12 months.

SERVICING INSTRUCTIONS

- Remove manhole cover.
- Remove MOE cartridge from housing.
- Wash out housing and funnel if necessary.
- Place new cartridge in housing and replace manhole cover.

Inventive Resources, Inc.
P.O. Box 1316
5038 Salida Blvd. Salida, CA 95368
Phone 209.545.1663 Fax 209.545.3533
Email: info@iriproducts.com

Rev 030617

